WFG50000 Series Water-Based Gravure Light Packaging Lamination Ink

1. Product Overview

WFG50000 Series is a premium water-based gravure lamination ink tailored for flexible light packaging. It is primarily applied to tissue pouches, plastic shopping bags, and diverse flexible film and bag converting. Formulated for rotogravure reverse printing on BOPP, CPP, and PE films followed by solventless or dry lamination, maintaining superb stability during high-speed printing.

2. Product Features

- High Color Density: Brilliant shade and high tinting strength.
- Outstanding Lamination Suitability: Compatible with dry and solventless lamination processes.
- High-Speed Press Stability: Excellent anti-misting and ink transfer at high line speeds.
- Fast Drying: Rapid drying rate preventing ink blocking and cylinder buildup.
- Precise Dot Sharpness: Outstanding dot reproduction across highlight and shadow tones.
- Eco-Friendly Formulation: Low-odor, low-VOC aqueous formula fulfilling modern packaging environmental requirements.

3. Suitable Substrates

Suitable for flexible packaging films including BOPP, CPP, PE, and related light packaging substrates.

4. Technical Specifications

The following data are typical values intended for product selection and technical reference only. Unless otherwise agreed in writing, they do not constitute guaranteed specifications.

Property	Unit	Typical Value	Test Method / Notes
Appearance & Color	-	Viscous liquid in various colors	Visual inspection
Viscosity	s	35–55	Zahn #2 cup, 25°C
pH Value	-	8.0–9.0	25°C
Solid Content	%	-	Oven drying, 120°C × 2 h
Gloss (60°)	GU	-	60° angle

5. Application Guidelines

Ink Preparation	Stir thoroughly for 5–10 minutes prior to use. Filtration through ≥200 mesh screen is recommended before loading onto press. 1-pack system; consume promptly after opening.
Plate / Cylinder Specs	Gravure / Lamination: cylinder screen 200–250 LPI, cell depth 32–40 μm, moderate doctor blade pressure.
Dilution Ratio	Standard diluent: Ethanol:Deionized Water = 9:1, dilution ratio 35%–60% (adjust based on press speed and target operating viscosity).
Press Viscosity	17–25 s (Zahn #2 cup, 25°C).
Press Speed	80–160 m/min (suitable for high-speed printing; optimize based on press model and drying capacity).
Drying Method	Hot air drying, air temperature 60–90°C; ensure complete drying before rewinding.
Equipment Cleaning	Clean printing plates and ink circulating systems promptly after printing with diluent or dedicated aqueous cleaning agents to prevent ink drying and clogging.
Application Note	Prior to initial commercial production, thorough trials must be conducted under actual operating conditions to verify ink adhesion, drying profile, and post-finishing compatibility on target substrates.

6. Regulatory & Safety

Regulatory Compliance	Complies with RoHS and REACH (SVHC) directives.
Food Contact Statement	Formulated for external non-food-contact secondary packaging. If specialized food contact compliance or low-migration performance is required, project-specific technical evaluation and formulation confirmation by Haocai are required.
Usage Note	VOC content complies with China national standard GB 38507-2020.
Safety Data Sheet (SDS)	Safety Data Sheets (SDS) are available upon request.
User Responsibility	Users must independently verify product suitability, regulatory compliance, and processing performance under actual commercial production conditions prior to full-scale adoption.

7. Packaging & Storage

Standard Packaging	20 kg / 25 kg plastic pails; 1,000 kg IBC containers (custom packaging available upon request).
Storage Conditions	Store tightly sealed in original containers. Keep in a dry, cool, and well-ventilated warehouse at 5–35°C, away from direct sunlight and rain. Strictly protect from freezing; prevent winter frost damage or high-temperature degradation.
Shelf Life	12 months from production date in unopened original containers.
Post-Opening Care	Reseal immediately and tightly after dispensing; recommended to use within 6 months.

8. Typical Product Grades

Product Code	Key Features	Suitable Substrates	Target Applications
WFG50000 Series	High color density / Lamination compatibility / High-speed stability	BOPP, CPP, PE films	Tissue paper pouches / Plastic bags / Flexible packaging film products

1. Baseline Platforms & Customization: The products listed above are core baseline platforms proven through extensive commercial mass production. To meet specific press speeds (e.g., ultra-high-speed inline coating), substrate absorbency variations, or demanding rub/crease-crack resistance requirements, Haocai provides tailored viscosity adjustments, customized additive packages, and bespoke functional performance development.

2. Specialty Process Integration: If specialized finishes such as drip-off / drip-relief combination effects or tactile matte finishes are required, please contact Haocai technical support for a comprehensive turnkey printing formulation.

9. Disclaimer

The information contained herein is based on our current knowledge and experience and is provided in good faith for general application guidance only. It does not constitute a legal warranty, guarantee, or binding technical specification. Users are strictly responsible for evaluating and confirming product suitability, process compatibility, and commercial usability under their actual operating conditions and production equipment prior to commercial use.